


Sharp Signage Display

# SHARP MULTISYNC® M982 LCD 98" MESSAGE LARGE FORMAT DISPLAY



The versatile solution for professional display applications, the Sharp MultiSync® M2 Series (32" up to 98") is purpose-built for demanding signage and meeting room environments.

- Seamless meeting workflows – a single USB-C cable transmits video, data, and power for instant, clutter-free meeting setups. As the established standard for modern collaboration spaces, USB-C supports frictionless BYOD experiences.
- Unhindered readability – a high-haze panel reduces glare from windows and ambient light, keeping signage content and presentations clear for uninterrupted viewing in any environment.
- Security assured – 802.1x support over LAN enables high-level security for corporate networks, giving peace of mind for IT teams and enterprise environments.
- Enhanced imaging precision – when brand consistency and corporate identity are important, NEC's SpectraView Engine provides full control over colour, gamma, and uniformity for accurate and impactful content.
- Broad AV compatibility – fully interoperable with leading meeting room platforms including Crestron (XiO Cloud), Cisco Webex, Q-Sys, and Microsoft Teams, ensuring effortless integration and future-proof scalability.

# Specifications

## Panel Data

Panel Response Time (ms)

8

## Accessories

Accessories

Eco Sensor, Feet, Wall mount, USB-C cable, Trolley, Speaker, Remote control kit Power Cable, Remote Control, HDMI Cable, 2 x AAA batteries, Setup Manual, Display

## Display Module Data

Panel Technology

IPS with Direct LED backlights

Native Resolution (Pixels)

3840 x 2160

Aspect Ratio

16:9:0:0

Brightness (cd/m<sup>2</sup>)

550

Contrast Ratio

8000:1

Viewing Angle (°)

178

Colour Depth [bit]

1073 (10bit)

Response Time (typ.) [ms]

8

## Additional Features

Colour Versions

Black Back Cabinet, Black Front Bezel

Safety and Ergonomics

EMC Class B, UKCA, ISO 9241-307

(pixel failure class I), RoHS, UL/C-

UL or CSA, FCC Class B, CE,

EnergyStar 8.0, REACH

optional 4th to 5th year warranty

extension, Additional services

available, 3 years warranty incl.

backlight

## Weights and Measures

Shipping Carton Dimensions (Width) mm

2350

Shipping Carton Dimensions (Height) mm

1400

Shipping Carton Dimensions (Depth) mm

310

Shipping Weight (Kg)

99

## Touch Interface Specification

Haze Level [%]

Pro 25

## Synchronisation Rate

Horizontal Frequency [kHz]

15 - 135

Vertical Frequency [Hz]

23 - 76

## Connectivity

Digital

DisplayPort, DisplayPort out, HDMI, USB Type C

Output Control

LAN 100Mbit

## Environmental Conditions

Operating Humidity (min) [%]

20

Operating Humidity (max) [%]

80

## Ergonomics

Landscape Dimensions (Width) [mm]

2195

Landscape Dimensions (Height) [mm]

1250

Landscape Dimensions (Depth) [mm]

84

## Projectors

Weight (kg)

68

## Installation

Portrait Installation

True

Landscape Installation

True

Landscape

True

Portrait

True

Mounting (VESA mm)

600 x 400 (FDMI)

Mounting (Number of Points/Pitch)

4

Mounting Screw Specification (Size/Max Length)

M8

Face up

True

## Key Specifications

Special Characteristics

CEC Support, DICOM Simulation, Clone Settings, HDMI ARC, Scheduler

24/7 Operation Certified

True

Built in Speakers (W)

10 + 10

Power Management

True

Temperature Sensor

True

Brightness Sensor

True

Remote Management

True

Operating Time

24/7

## Power Supply and Operating Environment

Operating Voltage (ACV)

100-240

Frequency (Hz)

50-60

Via AC Adapter

True

Operating Voltage (DCV)

100-240

Operating Temperature (°C)

0 - 40

Storage Temperature (°C)

-20 - 60

Storage Humidity Min [%]

10

Storage Humidity Max [%]

80

Power Saving Mode (W)

< 2 (Networked Standby)

Battery

< 0.5 (ECO Standby)

## Display

Screen Size (inch)

98

Screen Size (cm)

247

Colour Gamuts

72% NTSC

## Resolution

Supported Resolution

1024 x 768 , 1920 x 1200, 1400 x 1050, 1366 x 768, 720 x 480, 720 x 400, 720 x 576, 1360 x 768, 3840 x 2160, 4096 x 2160, 1680 x 1050, 1280 x 720, 800 x 600, 640 x 480, 1920 x 1080, 1600 x 1200, 1280 x 1024, 1440 x 900, 1280 x 800

## Electrical

Power Supply

100-240 V

## Mechanical

Bezel Width (Left/Right) [mm]

16

Bezel Width (Upper) [mm]

16

Bezel Width (Lower) [mm]

16

## Green Features

Energy Efficiency

LED backlight technology, Energy efficiency class: G

Ecological Standards

Energy Star 8.0



**4K UHD**  
READY

**CRESTRON**

NaViSet  
Administrator 2

**SpectraView**  
engine

**USB Type-C**

Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett-Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O: Ref: Sharp MultiSync® M982 LCD 98" Message Large Format Display, 3/2026